

2wcom RDS Encoder now even more flexible with multiple IP ports

Date: 07-20-2009 04:15 PM CET

Category: [Media & Telecommunications](#)

Press release from: [2wcom GmbH](#)

With programmable Automation Interface and multiple IP ports the 2wcom RDS Encoder is now even more flexible.

The programmable Automation Interface allows broadcasters to feed in song title / artist information directly – serial or alternatively via TCP/IP. The advantage of the 2wcom Automation Interface is that it can be configured to adapt to the standard studiosoftware.

The 2wcom RDS Encoder achieves further flexibility by the upgrade to five IP ports. One port can be used exclusively by the Automation Interface. The four additional ports are available for freely selectable applications like Traffic Message Service (TMC), Early Warning System (EWS), Radiotext / PI or customized protocols like weather data.

Improved functionality and customer orientation were also our main objectives when updating the RDS Encoder configuration software Arcos Config. With Arcos Config the 2wcom software team has developed an extremely user friendly operation software.

About 2wcom GmbH

The 2wcom GmbH has been established for years as worldwide supplier of professional broadcast products in the fields of FM, RDS, DVB and TCP/IP-SNMP Management Control. With a team of experienced engineers and technicians 2wcom develops sophisticated solutions for decoding, monitoring, controlling, alerting, rebroadcasting, mobile monitoring and RDS encoding. All developments, from single components as well as complete devices to quality control are made on-site.

2wcom GmbH
Lise-Meitner-Straße 4
24941 Flensburg
Germany
presse@2wcom.com

[You can find this press release here](#)